## NSN 5930-01-257-8128

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-257-8128

Body Style:
Panel mount
Overall Length:
1.200 inches
Overall Height:
2.968 inches
Overall Width:
0.960 inches
Body Length:
1.090 inches
Body Width:
0.850 inches
Body Height:
1.750 inches
Actuator Length:
Between 1.020 inches and 1.035 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.164 inches and 0.210 inches
Actuator Width:
Between 0.607 inches and 0.630 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Amber single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Special Features:
Emi screen
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

6 turret and 5 tab solder lug

## NSN 5930-01-257-8128

Push Switch - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

81349-mil-s-22885/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0