

View Online at <https://aerobasegroup.com/nsn/5930-01-257-9796>

Body Style:

Bushing mount

Bushing Length:

0.470 inches

Body Length:

0.575 inches

Body Width:

0.535 inches

Actuator Style:

Round

Actuator Diameter:

0.429 inches

Actuator Height:

1.160 inches

Actuator Position-action Relationship:

Center position maintained and left position momentary and right position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

0.740 inches

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0