

View Online at <https://aerobasegroup.com/nsn/5930-01-258-1430>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.560 inches single mounting facility

**Width Between Flats:**

0.217 inches single actuator

**Overall Length:**

Between 3.390 inches and 4.450 inches

**First Flat Length:**

0.312 inches single actuator

**Shaft Diameter:**

0.314 inches single actuator

**Shaft Length:**

0.370 inches single actuator

**Overall Diameter:**

1.750 inches

**Nonturn Device Radius:**

0.625 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thready Qty Per Inch (tpi):**

20 single mounting facility

**Thread Size:**

0.500 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, parallel flatted, threaded hole single actuator

**Terminal Type:**

Quick disconnect, male

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level and 10.0 amperes inductive load dc at sea level and 5.0 amperes lamp load dc at sea level

**Style Designator:**

Snap or line

**Test Data Document:**

81349-mil-s-13623 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single mounting facility

**Specification Data:**

81349-mil-s-13623/1-3 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0