

View Online at <https://aerobasegroup.com/nsn/5930-01-258-1430>

Thread Class:

2a single mounting facility

Thread Length:

0.560 inches single mounting facility

Width Between Flats:

0.217 inches single actuator

Overall Length:

Between 3.390 inches and 4.450 inches

First Flat Length:

0.312 inches single actuator

Shaft Diameter:

0.314 inches single actuator

Shaft Length:

0.370 inches single actuator

Overall Diameter:

1.750 inches

Nonturn Device Radius:

0.625 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.500 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Quick disconnect, male

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level and 10.0 amperes inductive load dc at sea level and 5.0 amperes lamp load dc at sea level

Style Designator:

Snap or line

Test Data Document:

81349-mil-s-13623 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf single mounting facility

Specification Data:

81349-mil-s-13623/1-3 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0