

View Online at <https://aerobasegroup.com/nsn/5930-01-258-8709>

Overall Length:

12.560 inches

Overall Height:

2.810 inches

Overall Width:

2.810 inches

First Flat Length:

0.380 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.380 inches single actuator

Unthreaded Mounting Hole Diameter:

0.213 inches single mounting facility

Individual Section Quantity:

25

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.625 inches single mounting facility

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, nonparallel flatted single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-21604/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0