

View Online at <https://aerobasegroup.com/nsn/5930-01-259-0819>

Overall Length:

4.000 inches

Overall Height:

6.250 inches

Overall Width:

4.125 inches

Body Height:

6.250 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Mounting Facility Centers:

3.250 inches

Capillary Tube Length:

48.0 inches

Bulb Length:

15.375 inches

Bulb Diameter:

0.188 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between 60.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Cubic Measure:

71.875 cubic inches

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action

Terminal Type:

Threaded stud

Contact Load Current Rating:

30.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+60.00/+250.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Special Features:

Three additional mounting holes 0.156 in. diameter; holes arranged in the shape of isosceles triangle; longest horizontal distance between centers 1.938 in. Nom; longest vertical distance between centers 3.250 in. Nom; shortest horizontal distance between centers 0.969

Media For Which Designed:

Gas or liquid or solid

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0