NSN 5930-01-259-1997

Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-259-1997

| Hazardous Locations/environmental Protection: |
|---|
| Vibration resistant |
| Overall Length: |
| 3.875 inches |
| Overall Height: |
| 4.750 inches |
| Overall Width: |
| 2.188 inches |
| Mounting Method: |
| Inlet connection and outlet connection |
| Features Provided: |
| Hermetically sealed case |
| Contact Action Stimulus: |
| Decrease |
| Thread Size: |
| 1.250 inches all threaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Wire lead |
| Contact Load Current Rating: |
| 500.0 milliamperes resistive load second voltage and 500.0 milliamperes inductive load second voltage |
| Contact Adjustability: |
| Actuation point not adjustable |
| Contact Stimulus Rating: |
| 18.00 actuation point gallons per minute |
| Contact Voltage Rating In Volts: |
| 6.0 dc at sea level first voltage |
| Media For Which Designed: |
| Gas or liquid |
| Thread Series Designator: |
| Npt all threaded hole |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A048b0 |