NSN 5930-01-259-1998

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-259-1998

Hazardous Locations/environmental Protection: Shock resistant and salt spray resistant and vibration resistant **Overall Length:** 0.549 inches **Overall Diameter:** 0.550 inches **Individual Section Quantity:** 1 **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Switch Contact Basic Design: Nonpile-up symmetrical **Pole Quantity:** 1 single section rear **Throw Quantity:** 5 single section rear **Mounting Method:** Terminal single mounting facility **Features Provided:** Actuator knob **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Terminal Type:** Pin **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 36.0 degrees single actuator **Detent Rotational Torque Range:** +1.000/+8.000 inch-ounces single actuator **Contact Load Current Rating:** 250.0 milliamperes resistive load dc at sea level Style Designator: Miniature, pin mount, integral knob Shelf Life: N/a Unit Of Measure: ---**Demilitarization:**

No

NSN 5930-01-259-1998

Rotary Switch - Page 2 of 2

Fiig: A052b0

