

View Online at <https://aerobasegroup.com/nsn/5930-01-259-2688>

Thread Class:

2a single mounting facility

Thread Length:

0.365 inches single mounting facility and 0.380 inches single mounting facility

Overall Length:

2.350 inches

First Flat Length:

0.280 inches single actuator

Flat Height:

0.211 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.370 inches single actuator and 0.385 inches single actuator

Overall Diameter:

1.380 inches

Individual Section Quantity:

2

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Pile-up

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

5.0 lowest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Contact Load Current Rating:

1.0 milliamperes resistive load lowest dc voltage rating at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A052b0