

View Online at <https://aerobasegroup.com/nsn/5930-01-259-2689>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.365 inches single mounting facility and 0.380 inches single mounting facility

**Overall Length:**

2.475 inches

**First Flat Length:**

0.450 inches single actuator

**Flat Height:**

0.211 inches single actuator and 0.221 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.495 inches single actuator and 0.510 inches single actuator

**Overall Diameter:**

1.380 inches

**Nonturn Device Radius:**

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Pile-up

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

5.0 lowest dc voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section in-line

**Contact Load Current Rating:**

1.0 milliamperes resistive load lowest dc voltage rating at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Une single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0