NSN 5930-01-259-3304

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-259-3304

Thread Class: 2a all threaded hole **Overall Length:** 2.532 inches **Distance Between Mounting Facility Centers:** 1.438 inches **Capillary Tube Length:** 48.0 inches **Bulb Length:** 11.000 inches **Tempurature Sensing Element Type:** Capillary tube-bulb **Mounting Method:** Bracket and threaded hole Thready Qty Per Inch (tpi): 32 all threaded hole **Contact Action Stimulus:** Increase **Thread Size:** 0.164 inches all threaded hole **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 2 pole, single throw, normally open, momentary action **Terminal Type:** Quick disconnect, male **Contact Load Current Rating:** 15.0 amperes resistive load first voltage **Contact Adjustability:** Actuation point adjustable and deactuation point adjustable **Contact Adjustment Type:** External actuation point shaft and external deactuation point shaft **Contact Voltage Rating In Volts:** 240.0 ac at sea level second voltage **Special Features:** Three-position selction3cthf1bjamb17.0 Media For Which Designed: Gas or liquid **Thread Series Designator:** Unc all threaded hole Shelf Life:

N/a

NSN 5930-01-259-3304

Thermostatic Switch - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0