

View Online at <https://aerobasegroup.com/nsn/5930-01-259-3722>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.810 inches

Overall Height:

2.394 inches

Overall Width:

2.125 inches

Unthreaded Mounting Hole Diameter:

0.140 inches single mounting facility

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.490 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.700 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7 each section

Contact Arrangement Truth Table:

Bcd, 1 pole - 8 positions each section

Color:

White each indicator marking

Precious Material And Location:

Contacts gold and contacts platinum and contacts silver

Precious Material:

Gold and platinum and silver

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0