## NSN 5930-01-259-3733



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-259-3733 **Body Style:** Panel mount **Body Length:** 0.689 inches **Body Width:** 0.689 inches **Body Height:** 2.240 inches **Actuator Length:** 0.625 inches **Actuator Style:** Rectangular **Actuator Height:** 0.150 inches **Actuator Width:** 0.625 inches **Actuator Color:** Black single actuator **Illuminated Actuator Color:** White single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Nonpile-up Contact Arrangement:** 3 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 1.000 amperes resistive dc and 500.000 milliamperes inductive dc **Precious Material And Location:** Contacts gold **Test Data Document:** 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 tab, solder lug and 9 turret **Specification Data:** 

N/a

Shelf Life:

**Unit Of Measure:** 

81349-mil-s-22885/90 government specification

## NSN 5930-01-259-3733

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0