

View Online at <https://aerobasegroup.com/nsn/5930-01-259-3734>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Shock proof and vibration resistant

Overall Length:

3.234 inches

Overall Height:

1.200 inches

Overall Width:

0.960 inches

Body Width:

0.800 inches

Body Height:

1.090 inches

Actuator Length:

1.040 inches

Actuator Style:

Rectangular

Actuator Height:

0.140 inches

Actuator Width:

Between 0.610 inches and 0.630 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

Green single actuator and red single actuator

Illuminated Actuator Color Sequence:

Top half of actuator green bottom half of actuator red

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.094 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Test Data Document:

81349-mil-s-22885/87 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Specification Data:

81349-mil-s-22885 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0