

View Online at <https://aerobasegroup.com/nsn/5930-01-259-3734>

**Body Style:**

Panel mounted

**Hazardous Locations/environmental Protection:**

Shock proof and vibration resistant

**Overall Length:**

3.234 inches

**Overall Height:**

1.200 inches

**Overall Width:**

0.960 inches

**Body Width:**

0.800 inches

**Body Height:**

1.090 inches

**Actuator Length:**

1.040 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.140 inches

**Actuator Width:**

Between 0.610 inches and 0.630 inches

**Actuator Color:**

White single actuator and white single actuator

**Illuminated Actuator Color:**

Green single actuator and red single actuator

**Illuminated Actuator Color Sequence:**

Top half of actuator green bottom half of actuator red

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

3.094 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Test Data Document:**

81349-mil-s-22885/87 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

12 turret and 5 tab, solder lug

**Specification Data:**

81349-mil-s-22885 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0