NSN 5930-01-259-7414

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-259-7414

Body Style:				
Panel mounted				
Hazardous Locations/environmental Protection:				
Driptight and dustproof and moisture resistant				
Overall Length:				
2.355 inches				
Overall Height:				
0.960 inches				
Overall Width:				
0.960 inches				
Body Width:				
0.750 inches				
Body Height:				
0.750 inches				
Case Material:				
Metal				
Actuator Length:				
0.620 inches				
Actuator Style:				
Rectangular				
Actuator Height:				
0.275 inches				
Actuator Width:				
0.620 inches				
Actuator Color:				
Black single actuator and black single actuator				
Illuminated Actuator Color:				
Green single actuator and yellow single actuator				
Actuator Inscription:				
Jf-pd wpn coor/calling single actuator				
Illuminated Actuator Color Sequence:				
Upper half of actuator yellow lower half of actuator green				
Maximum Voltage Rating In Volts:				
28.0 dc and 115.0 ac				
Mounting Surface To Terminal End Distance:				
Between 1.720 inches and 1.880 inches				
Inclosure Type:				
Fully enclosed				

Features Provided:

Panel

catales i lovidea.

Mounting Method:

Actuator seal and horizontal split lens

NSN 5930-01-259-7414

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

D!	NA-1:	AI I	
Precious	Materiai	And I	Location:

Contacts silver

Terminal Type And Quantity:

5 tab, solder lug and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0