## NSN 5930-01-259-7415

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-259-7415

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Driptight and dustproof and moisture resistant
Overall Length:
2.355 inches
Overall Height:
0.960 inches
Overall Width:
0.960 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.275 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Call release single actuator
Maximum Voltage Rating In Volts:
28.0 dc and 115.0 ac
Mounting Surface To Terminal End Distance:
Between 1.720 inches and 1.880 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and full display lens
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit

## NSN 5930-01-259-7415

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

5 tab, solder lug and 3 turret

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0