# NSN 5930-01-259-8546

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-259-8546

#### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Driptight and dustproof and moisture resistant

#### **Overall Length:**

2.355 inches

#### **Overall Height:**

0.960 inches

#### **Overall Width:**

0.960 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

### Actuator Length:

0.620 inches

### Actuator Style:

Rectangular

#### Actuator Height:

0.275 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

Black single actuator and black single actuator

#### **Illuminated Actuator Color:**

Green single actuator and yellow single actuator

#### **Actuator Inscription:**

Jf falg p and b/calling single actuator

#### Illuminated Actuator Color Sequence:

Upper half of actuator is yellow lower half of actuator is green

#### Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

#### Mounting Surface To Terminal End Distance:

Between 1.720 inches and 1.880 inches

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

#### **Features Provided:**

Actuator seal and horizontal split lens

# NSN 5930-01-259-8546

Push Switch - Page 2 of 2



#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

**Terminal Type And Quantity:** 

5 tab, solder lug and 3 turret

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0