NSN 5930-01-259-8785

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-259-8785

Hazardous Locations/environmental Protection	n:
--	----

Moisture resistant and vibration resistant

Overall Length:

1.187 inches

Overall Height:

0.380 inches

Body Diameter:

0.604 inches

Body Height:

0.290 inches

Unthreaded Mounting Hole Diameter:

Between 0.104 inches and 0.114 inches

Distance Between Mounting Facility Centers:

Between 0.927 inches and 0.947 inches

End Application:

4920-01-150-2037 analyzer unit, jet engine

Tempurature Sensing Element Type:

Internal sensor

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

50.0 milliamperes resistive load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

122.00 actuation point degrees fahrenheit and 104.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

50.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or solid

NSN 5930-01-259-8785

Thermostatic Switch - Page 2 of 2



Precious Material And Location:
Contacts gold
Precious Material:
Gold
Style Designator:
Disc w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0