

View Online at <https://aerobasegroup.com/nsn/5930-01-260-1121>

Body Style:

Bushing/hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.380 inches

Bushing Length:

0.150 inches

Body Length:

0.760 inches

Body Width:

0.470 inches

Body Height:

0.250 inches

Unthreaded Mounting Hole Diameter:

0.031 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.180 inches

Actuator Style:

Round

Actuator Diameter:

0.100 inches

Actuator Height:

0.060 inches

Actuator Free Position Height:

0.420 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

6525-01-224-0194

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Switch Release Force:

0.280 newtons

Switch Actuating Force:

2.8 newtons

Actuator Movement:

0.037 overtravel inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes inductive ac

Special Features:

Burgess k3 series

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0