

View Online at <https://aerobasegroup.com/nsn/5930-01-260-1121>

**Body Style:**

Bushing/hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.380 inches

**Bushing Length:**

0.150 inches

**Body Length:**

0.760 inches

**Body Width:**

0.470 inches

**Body Height:**

0.250 inches

**Unthreaded Mounting Hole Diameter:**

0.031 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.180 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.100 inches

**Actuator Height:**

0.060 inches

**Actuator Free Position Height:**

0.420 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**End Application:**

6525-01-224-0194

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Switch Release Force:**

0.280 newtons

**Switch Actuating Force:**

2.8 newtons

**Actuator Movement:**

0.037 overtravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes inductive ac

**Special Features:**

Burgess k3 series

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0