

View Online at <https://aerobasegroup.com/nsn/5930-01-260-1408>

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

1.810 inches

**Overall Height:**

0.406 inches

**Overall Width:**

2.125 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches single mounting facility

**Individual Section Quantity:**

2

**Longest Horizontal Distance Between Mounting Centers:**

1.490 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.700 inches single mounting facility

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

16 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f each section

**Contact Arrangement Truth Table:**

Special each section

**Special Truth Table Identification:**

01963-6 each section

**Color:**

White each indicator marking

**Precious Material And Location:**

Contacts gold and contacts platinum and contacts silver

**Precious Material:**

Gold and platinum and silver

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0