

View Online at <https://aerobasegroup.com/nsn/5930-01-260-1419>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

Between 0.859 inches and 0.891 inches

Bushing Length:

Between 0.422 inches and 0.453 inches

Body Length:

0.969 inches

Case Material:

Metal

Actuator Diameter:

Between 0.359 inches and 0.391 inches

Actuator Height:

Between 0.047 inches and 0.078 inches

Illuminated Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

30.0 dc

End Application:

4920-01-149-9950 collection unit, data

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc

Precious Material And Location:

Terminal surfaces gold

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0