

View Online at <https://aerobasegroup.com/nsn/5930-01-260-1419>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

Between 0.859 inches and 0.891 inches

**Bushing Length:**

Between 0.422 inches and 0.453 inches

**Body Length:**

0.969 inches

**Case Material:**

Metal

**Actuator Diameter:**

Between 0.359 inches and 0.391 inches

**Actuator Height:**

Between 0.047 inches and 0.078 inches

**Illuminated Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

30.0 dc

**End Application:**

4920-01-149-9950 collection unit, data

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc

**Precious Material And Location:**

Terminal surfaces gold

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0