

View Online at <https://aerobasegroup.com/nsn/5930-01-260-2851>

**Thread Class:**

3b single pressure connection

**Inside Diameter:**

0.438 inches single connection

**Hazardous Locations/environmental Protection:**

Corrosion resistant and explosion proof and humidity resistant

**Overall Length:**

4.370 inches

**Body Diameter:**

1.440 inches

**Overall Diameter:**

1.500 inches

**Unthreaded Mounting Hole Diameter:**

0.210 inches

**Distance Between Mounting Facility Centers:**

1.120 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 80.0 degrees celsius

**Mounting Method:**

Base and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4500.00 pounds per square inch gage

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

2.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

2000.00 actuation point pounds per square inch gage and 1700.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0