

View Online at <https://aerobasegroup.com/nsn/5930-01-260-2851>

Thread Class:

3b single pressure connection

Inside Diameter:

0.438 inches single connection

Hazardous Locations/environmental Protection:

Corrosion resistant and explosion proof and humidity resistant

Overall Length:

4.370 inches

Body Diameter:

1.440 inches

Overall Diameter:

1.500 inches

Unthreaded Mounting Hole Diameter:

0.210 inches

Distance Between Mounting Facility Centers:

1.120 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -55.0 degrees celsius and 80.0 degrees celsius

Mounting Method:

Base and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

2000.00 actuation point pounds per square inch gage and 1700.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0