NSN 5930-01-260-3753

Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-260-3753

Overall Length:
2.875 inches
Mounting Method:
Line and threaded bushing
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Decrease
Thread Size:
0.500 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
90.0 milliamperes resistive load first voltage
Contact Adjustability:
Actuation point not adjustable
Contact Stimulus Rating:
3.80 actuation point gallons per minute
3.80 actuation point gallons per minute Contact Voltage Rating In Volts:
Contact Voltage Rating In Volts:
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed:
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator:
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing Shelf Life:
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing Shelf Life: N/a
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing Shelf Life: N/a
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing Shelf Life: N/a Unit Of Measure:
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing Shelf Life: N/a Unit Of Measure: Demilitarization:
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing Shelf Life: N/a Unit Of Measure: Demilitarization: No
Contact Voltage Rating In Volts: 6.0 dc at sea level third voltage Media For Which Designed: Liquid Thread Series Designator: Npt single threaded bushing Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: