

View Online at <https://aerobasegroup.com/nsn/5930-01-260-5272>

Thread Class:

2a single mounting facility

Thread Length:

0.417 inches single mounting facility and 0.457 inches single mounting facility

Overall Length:

2.944 inches

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

0.417 inches single actuator and 0.457 inches single actuator

Overall Diameter:

1.312 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

12 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0