

View Online at <https://aerobasegroup.com/nsn/5930-01-260-5272>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.417 inches single mounting facility and 0.457 inches single mounting facility

**Overall Length:**

2.944 inches

**Shaft Diameter:**

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:**

0.417 inches single actuator and 0.457 inches single actuator

**Overall Diameter:**

1.312 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Slotted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

12 single section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0