

View Online at <https://aerobasegroup.com/nsn/5930-01-260-6491>

**Thread Class:**

2a single mounting facility

**Overall Length:**

1.946 inches

**Overall Height:**

1.000 inches

**Overall Width:**

0.906 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.211 inches single actuator and 0.221 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Nonturn Device Radius:**

0.375 inches at 3:00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded hole single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 lowest dc voltage rating at sea level

**Rotor Through Connection Quantity:**

2 each section

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Contact Load Current Rating:**

700.0 milliamperes resistive load lowest dc voltage rating at sea level

**Precious Material And Location:**

Terminals and rotor contact silver and terminal surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0