NSN 5930-01-260-7788

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-260-7788

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Waterproof

Body Length:

0.975 inches

Body Width:

0.975 inches

Body Height:

3.150 inches

Case Material:

Plastic

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

11 pin

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5930-01-260-7788

Push Switch - Page 2 of 2

Fiig: A053a0

