

View Online at <https://aerobasegroup.com/nsn/5930-01-260-8715>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.242 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.875 inches single actuator

Overall Diameter:

0.562 inches

Individual Section Quantity:

6

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

End Application:

1095-01-235-3139

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 6th section rear

Throw Quantity:

1 1st section front

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thready Qty Per Inch (tpi):

28 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Switch Actuator Indexing Position Quantity:

1 single actuator

Shaft Type:

Round, flatted w/through hole single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Un single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0