## NSN 5930-01-261-6420

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

**Body Style:**Panel mounted

Overall Length: 3.390 inches Overall Height: 1.490 inches



View Online at https://aerobasegroup.com/nsn/5930-01-261-6420

Overall Width:
1.240 inches
Body Width:
0.900 inches
Body Height:
1.162 inches
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.240 inches
Actuator Width:
0.750 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator and white single actuator
Actuator Inscription:
On, keyboard single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator green, lower half of actuator white
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
3.150 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal and horizontal split lens
Nonpile-up Contact Arrangement:
4 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

## NSN 5930-01-261-6420

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

**Special Features:** 

Emi shielding

**Precious Material And Location:** 

Contact surfaces silver

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

Fiig:

A053a0