

View Online at <https://aerobasegroup.com/nsn/5930-01-261-6420>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.390 inches

Overall Height:

1.490 inches

Overall Width:

1.240 inches

Body Width:

0.900 inches

Body Height:

1.162 inches

Actuator Length:

1.000 inches

Actuator Style:

Rectangular

Actuator Height:

0.240 inches

Actuator Width:

0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Green single actuator and white single actuator

Actuator Inscription:

On, keyboard single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator green, lower half of actuator white

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

3.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and horizontal split lens

Nonpile-up Contact Arrangement:

4 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Emi shielding

Precious Material And Location:

Contact surfaces silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0