NSN 5930-01-261-6420

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Explosion proof and humidity resistant

Body Style:Panel mounted

Overall Length: 3.390 inches Overall Height: 1.490 inches



View Online at https://aerobasegroup.com/nsn/5930-01-261-6420

| Overall Width: |
|--|
| 1.240 inches |
| Body Width: |
| 0.900 inches |
| Body Height: |
| 1.162 inches |
| Actuator Length: |
| 1.000 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.240 inches |
| Actuator Width: |
| 0.750 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Green single actuator and white single actuator |
| Actuator Inscription: |
| On, keyboard single actuator |
| Illuminated Actuator Color Sequence: |
| Upper half of actuator green, lower half of actuator white |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 3.150 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal and horizontal split lens |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit |
| |
| |

NSN 5930-01-261-6420

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Special Features:

Emi shielding

Precious Material And Location:

Contact surfaces silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A053a0