NSN 5930-01-261-6423

Push Switch - Page 1 of 2

Special Features:

Emi shielding; split lens; guard included



View Online at https://aerobasegroup.com/nsn/5930-01-261-6423

| Body Style: |
|---|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Waterproof |
| Overall Length: |
| 1.490 inches |
| Overall Width: |
| 1.390 inches |
| Body Length: |
| 1.162 inches |
| Body Width: |
| 1.062 inches |
| Body Height: |
| 3.150 inches |
| Actuator Length: |
| 1.000 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.240 inches |
| Actuator Width: |
| 0.750 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Red single actuator and white single actuator |
| Actuator Inscription: |
| Alarm, override single actuator |
| Illuminated Actuator Color Sequence: |
| Upper half of actuator red, lower half of actuator white |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 1.000 amperes resistive dc and 0.500 amperes inductive dc |

NSN 5930-01-261-6423

Push Switch - Page 2 of 2



| Precious | Material | And | Location: |
|----------|----------|------------|-----------|
| | | | |

Contact surfaces gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0