

View Online at <https://aerobasegroup.com/nsn/5930-01-261-6424>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.390 inches

Overall Height:

1.490 inches

Overall Width:

1.390 inches

Body Width:

1.062 inches

Body Height:

1.162 inches

Case Material:

Metal

Actuator Length:

1.000 inches

Actuator Style:

Rectangular

Actuator Height:

0.240 inches

Actuator Width:

0.750 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator and white single actuator

Actuator Inscription:

Error, load single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator red, lower half of actuator white

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

3.150 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and horizontal split lens

Nonpile-up Contact Arrangement:

4 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Emi shielding; guard included

Precious Material And Location:

Contact surfaces gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0