NSN 5930-01-261-6424

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-01-261-6424

Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.390 inches
Overall Height:
1.490 inches
Overall Width:
1.390 inches
Body Width:
1.062 inches
Body Height:
1.162 inches
Case Material:
Metal
Actuator Length:
1.000 inches
Actuator Style:
Rectangular
Actuator Height:
0.240 inches
Actuator Width:
0.750 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator and white single actuator
Actuator Inscription:
Error, load single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator red, lower half of actuator white
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
3.150 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:

catales i lovidea.

Actuator seal and horizontal split lens

NSN 5930-01-261-6424

Push Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

4 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Emi shielding; guard included

Precious Material And Location:

Contact surfaces gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A053a0