

View Online at <https://aerobasegroup.com/nsn/5930-01-261-9586>

Thread Class:

2a

Body Style:

Bushing mount

Overall Height:

2.950 inches

Bushing Length:

0.500 inches

Body Length:

1.300 inches

Body Width:

0.670 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.300 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked out and down position no locking action and center position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.150 inches

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Thread Series Designator:

Unef

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0