## NSN 5930-01-262-6844

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-262-6844

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.520 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.101 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.312 inches
Actuator Length:
0.250 inches
Actuator Style:
Rectangular
Actuator Height:
0.188 inches
Actuator Width:
0.297 inches
Actuator Free Position Height:
0.0938 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Switch Release Force:
4.0 ounces
Switch Actuating Force:
8.0 ounces
Actuator Movement:
Between 0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a

## NSN 5930-01-262-6844

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

