

View Online at <https://aerobasegroup.com/nsn/5930-01-262-6844>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.520 inches

**Body Length:**

1.250 inches

**Body Width:**

0.500 inches

**Body Height:**

0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.101 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.312 inches

**Actuator Length:**

0.250 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.188 inches

**Actuator Width:**

0.297 inches

**Actuator Free Position Height:**

0.0938 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

8.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.015 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac and 10.000 amperes inductive ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0