NSN 5930-01-262-8418

Electrical Switch Retainer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-262-8418

1.560 inches Overall Width: 1.560 inches Unthreaded Mounting Hole Diameter: 0.453 inches second mounting facility End Application: 4925-01-207-1976 Mounting Facility Type And Quantity: 3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification: Qq-a-250/11, 1651 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 or 16511 federal specification single material response or qq-a-200/8, 1651 o	
1.560 inches Unthreaded Mounting Hole Diameter: 0.453 inches second mounting facility End Application: 4925-01-207-1976 Mounting Facility Type And Quantity: 3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification:	
Unthreaded Mounting Hole Diameter: 0.453 inches second mounting facility End Application: 4925-01-207-1976 Mounting Facility Type And Quantity: 3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification:	
0.453 inches second mounting facility End Application: 4925-01-207-1976 Mounting Facility Type And Quantity: 3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification:	
End Application: 4925-01-207-1976 Mounting Facility Type And Quantity: 3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification:	
4925-01-207-1976 Mounting Facility Type And Quantity: 3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification:	
Mounting Facility Type And Quantity: 3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification:	
3 unthreaded hole second mounting facility Material: Aluminum alloy 6061 Material Specification:	
Material: Aluminum alloy 6061 Material Specification:	
Aluminum alloy 6061 Material Specification:	
Material Specification:	
Qq-a-250/11, t651 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single material response or qq-a-200/8, t651 or t6511 federal specification single specifi	
	naterial response
Surface Treatment:	
Paint	
Surface Treatment Specification:	
Mil-t-704, type g military specification single treatment response and mil-c-46168, forest green color military specification si	ingle treatment
response	
Style Designator:	
Right angle, hole mounted	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A062a0	
Mil-std (military Standard):	
Mil-t-704 spec.	