

View Online at <https://aerobasegroup.com/nsn/5930-01-262-9734>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

5.500 inches

Overall Height:

4.000 inches

Overall Width:

4.938 inches

Body Height:

3.250 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.500 inches

End Application:

2840-01-196-4281 transition casing

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -40.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

250.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.00/+200.00 actuation point pounds per square inch and +0.00/+200.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point dial and internal deactuation point dial

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0