

View Online at <https://aerobasegroup.com/nsn/5930-01-262-9735>

Hazardous Locations/environmental Protection:

Moisture resistant and vibration resistant

Overall Length:

Between 6.350 inches and 6.412 inches

Overall Height:

1.500 inches

Overall Width:

1.500 inches

Body Length:

Between 6.250 inches and 6.312 inches

Unthreaded Mounting Hole Diameter:

0.209 inches

Distance Between Mounting Facility Centers:

1.120 inches

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

Between 32.0 degrees fahrenheit and 132.0 degrees fahrenheit

Mounting Method:

Threaded bushing and surface and unthreaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches first threaded bushing

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+84.00/+132.00 actuation point degrees fahrenheit

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

115.00 actuation point degrees fahrenheit and 10.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt first threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0