NSN 5930-01-262-9739

Push Switch - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5930-01-262-9739
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
1.200 inches
Overall Height:
2.828 inches
Overall Width:
0.960 inches
Body Length:
0.844 inches
Body Width:
0.850 inches
Body Height:
2.628 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
1430-01-181-5884 battery command post
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Test Data Document:
81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
6 turret and 6 tab, solder lug
Specification Data:
81349-mil-s-22885/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: