NSN 5930-01-262-9740

Push Switch - Page 1 of 2

Body Style: Panel mount



View Online at https://aerobasegroup.com/nsn/5930-01-262-9740

Hazardous Locations/environmental Protection:
Driptight and dustproof
Overall Length:
0.960 inches
Overall Height:
2.360 inches
Overall Width:
0.960 inches
Body Length:
0.750 inches
Body Width:
0.750 inches
Body Height:
1.095 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.150 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator
Illuminated Actuator Color:
Black single actuator
Actuator Inscription:
On single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit

NSN 5930-01-262-9740

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0