

View Online at <https://aerobasegroup.com/nsn/5930-01-263-5021>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

7.000 inches

Overall Height:

6.750 inches

Overall Width:

6.750 inches

Unthreaded Mounting Hole Diameter:

0.375 inches single mounting facility

Individual Section Quantity:

5

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

3.315 inches single mounting facility

Mounting Method:

Unthreaded hole single mounting facility and bracket single mounting facility

Features Provided:

Actuator knob and legend plate

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-s-15743/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0