## NSN 5930-01-263-5027

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-263-5027

**Thread Class:** 2b 1st mounting facility Thread Length: 0.438 inches 2nd mounting facility **Overall Length:** 5.030 inches **Overall Height:** 2.810 inches **Overall Width:** 2.810 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 2.300 inches 1st mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.300 inches 1st mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 15 each section rear **Mounting Facility Circle Radius:** 0.905 inches 2nd mounting facility **Mounting Method:** Threaded stud 2nd mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 1st mounting facility **Thread Size:** 0.190 inches 2nd mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Four position rectangular 1st mounting facility **Switch Actuator Indexing Position Quantity:** 16 single actuator **Terminal Type:** Screw

**Contact Switching Action:** 

Breaks before makes each section rear

## **NSN 5930-01-263-5027**Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:
22.5 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load ac at sea level
Precious Material And Location:
Rotor and stator surfaces silver
Precious Material:
Silver
Style Designator:
Tap, square frame
Test Data Document:
31349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef 2nd mounting facility
Specification Data:
31349-mil-s-21604/2 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A052b0