# NSN 5930-01-263-5027

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-263-5027

## **Thread Class:**

2b 1st mounting facility

## **Thread Length:**

0.438 inches 2nd mounting facility

## **Overall Length:**

5.030 inches

### **Overall Height:**

2.810 inches

**Overall Width:** 

2.810 inches

## Individual Section Quantity:

5

#### Longest Horizontal Distance Between Mounting Centers:

2.300 inches 1st mounting facility

## Longest Vertical Distance Between Mounting Centers:

2.300 inches 1st mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

### **Pole Quantity:**

1 each section rear

### Throw Quantity:

15 each section rear

## Mounting Facility Circle Radius:

0.905 inches 2nd mounting facility

#### **Mounting Method:**

Threaded stud 2nd mounting facility

#### **Features Provided:**

Actuator knob

## Thready Qty Per Inch (tpi):

24 1st mounting facility

#### Thread Size:

0.190 inches 2nd mounting facility

## **Contact Voltage Rating In Volts:**

125.0 ac at sea level

# Mounting Facility Pattern:

Four position rectangular 1st mounting facility

# Switch Actuator Indexing Position Quantity:

16 single actuator

## **Terminal Type:**

Screw

**Contact Switching Action:** 

Breaks before makes each section rear

# NSN 5930-01-263-5027

Rotary Switch - Page 2 of 2



# Switch Actuator Positioning Increment:

22.5 degrees single actuator

# Switch Actuator Stop Device Type:

Adjustable stop single actuator

# Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

# Precious Material And Location:

Rotor and stator surfaces silver

## **Precious Material:**

Silver

## Style Designator:

Tap, square frame

# Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef 2nd mounting facility

## **Specification Data:**

81349-mil-s-21604/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A052b0