

View Online at <https://aerobasegroup.com/nsn/5930-01-263-5032>

Thread Class:

2b 1st mounting facility

Overall Length:

5.250 inches

Overall Height:

3.000 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.203 inches 2nd mounting facility

Distance Between Mounting Facility Centers:

2.094 inches 2nd mounting facility

Individual Section Quantity:

12

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.156 inches 1st mounting facility

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 1st mounting facility

Thread Size:

0.190 inches 1st mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc 1st mounting facility

Specification Data:

81349-mil-s-15291/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0